



Sliding Door - 100mm (Single & Double Glazing)		X						X
Double Sliding Door - 74mm (C Groove Sliding)	X							
70mm Sliding - 6mm & 5mm						X		
70mm Sliding - 4mm & 3mm	X					X		
80mm Sliding - 6mm		X				X		
80mm Sliding - 5mm		X						
80mm Sliding - 4mm & 3mm	X							
<b>Sliding &amp; Folding</b>								
Sliding & Folding - 5mm & 6mm		X						X
<b>Shop Front</b>								
100mm Shop Front - 6mm								X
76mm Shop Front - 5mm & 6mm		X						X
76mm Shop Front - 4mm								X
76mm Shop Front - 3mm	X							X
<b>Fixed Panel</b>								
41mm Fixed Panel - 6mm						X		X
41mm Fixed Panel - 5mm		X						X
C groove Fixed panel - 6mm		X				X		
C groove Fixed panel - 5mm		X						
<b>Misselinious</b>								
AL 20 -5mm	X							
AL 20 -6mm						X		
C 101T -5mm						X		
C 101T -6mm	X							
F & G - 5mm & 6mm	X							

1. **Main content** : rubber, stearic acid, ZnO, carbon black, light calcium carbonate, paraffin oil, other agents, vulcanization accelerator

2. EPDM has excellent resistance to ozone, weathering resistance, heat resistance, excellent electrical insulation properties, good chemical stability. EPDM has the lowest proportion among all kinds of rubber; it can absorb a lot of filler and oil but not influence its properties

3. **Physical properties** : hardness 70±5A, tensile strength≥8MPa, Elongation at break≥400%, low temperature-40 no damage

4. **Strip standard** : GBT 24498-2009 windows and doors, curtain c/wall sealing strip

Kandana

Panadura

Minuwangoda

077 3631203

011 2237667

077 3081340

038 2235556

077 9726062

011 2296560